

United Electronic Industries & NASA VMS

WHAT IS THE NASA VMS COMPLEX?

NASA's VMS (Vertical Motion Simulator) complex is a high-fidelity flight simulation system with the capacity to travel vertically and laterally with six degrees of freedom. The VMS provides real-time piloted simulation and realistic sensory cues through six ICAB (Interchangeable Cabin) systems that can be modified to simulate any vehicle, including those still in the design stage, which makes it an invaluable tool for the research and development of new flight vehicles. The VMS is also routinely used to train astronauts and pilots, as it provides a no-risk, low-cost hyperrealistic flight experience.



THE IMMEDIATE CHALLENGES

- 1 NASA needed the VMS's simulations to be extremely precise and accurate, since the VMS complex would be used to inform future aerospace vehicle design decisions and help astronauts and pilots learn vehicle controls and behavior.
- 2 DAQ and control hardware needed to be capable of collecting and storing a variety of real-time data and sending accurate response commands to ICAB instruments and displays, including inceptor systems (such as a pilot's stick and pedal), out-the-window graphics, and both modern electronic and traditional dial-type instrument panels.
- 3 NASA was having trouble synchronizing the transfer of input and output data, resulting in inaccurate simulations.

UEI'S PATHWAY TO SUCCESS FOR NASA VMS

- To guarantee reliable and rapid data collection, UEI installed RACKtangle I/O systems in all ICAB units, as well as in central VMS system interfaces.
- Using UEI software, the RACKtangles collect inputs from ICAB sensors, write them to memory in the VMS system, and update outputs based on the stored data and vehicle specifications. A clock signal sent to each RACKtangle initiates the periodic update of inputs and outputs and ensures that all RACKtangles are synchronized.
- By using low-latency UDP packets rather than TCP/IP, UEI software ensures that all data is refreshed on each cycle, which can be run at speeds up to 4 kHz.

END RESULT UEI HARDWARE HELPS THE VMS PRODUCE REAL-TIME, HIGHLY SYNCHRONIZED, HIGH-FIDELITY AEROSPACE FLIGHT SIMULATIONS.

- [WIN]** UEI hardware guarantees a high synchronization rate and minimal jitter, allowing for precise control.
- [WIN]** Fast and synchronized aDMAP data transfer ensures a smooth, efficient and real-world simulator.
- [WIN]** Thanks to UEI I/O hardware, the VMS can produce true-to-life simulations that inform the future of aerospace flight technology and prepare astronauts and pilots for flight in a minimal-risk environment.

ASK US HOW UEI CAN DO THE SAME FOR YOUR COMPANY!

