



⚠ Inside the molded P1 end must use double copper foil and solder the braid 360 degree to the shell .

PIN OUT

P1	J1	J2	J3	J4
32	Coaxial		1	
30			2	
9	Coaxial		1	
29			2	
7	Coaxial		1	
23			2	
2	Coaxial		1	
22			2	

7	Heat shrink tubing with marking. Color: Black.	PCS	4
6	Heat shrink tubing with marking. Color: White.	PCS	4
5	J1~J4 Conn: BNC jack. (RFI: RFB-1123-1)	SET	4
4	Outer molded: 45P PVC, Color: Black.	G	40
3	Screw: E4.0*30.5mm (#4-40UNC) molded Black.	PCS	2
2	P1 CONN: DB 37Pin Male, Inside black, Pin gold flash.	PCS	1
1	Cable: RG-58/U 20AWG 50ohm coaxial cable. (Belden: 8262 010500)	MM	
ITEM	DESCRIPTION	UNIT	QTY

X ±	X° ±	NAME:	
.X ±	.X° ±	W1	
.XX ±	.XX° ±	UNITS:	PART NO.:
		MM	DNA-CBL-261-BNC
		TITLE:	
		2021.07.31	
		APPD BY	CHECK BY
		DRAWN BY	
		SCALE	SHEET
		NONE	1/1
		REV.	A