



⚠ Inside the molded P1 end must use double copper foil and solder the braid 360 degree to the shell .

PIN OUT

P1		
32	Red	J1
30	Black	J2
29	Green	J3
9	Blue	J4
7	Yellow	J5
2	White	J6

6	Heat shrink tubing with marking . color : white .	PCS	6
5	J1 Conn: Banana jack, Red (Cal Test: CT3134-S-2) J2 onn: Banana jack, Black (Cal Test: CT3134-S-0) J3 Conn: Banana jack, Green (Cal Test: CT3134-S-5) J4 Conn: Banana jack, Blue (Cal Test: CT3134-S-6) J5 Conn: Banana jack, Yellow (Cal Test: CT3134-S-4) J6 Conn: Banana jack, White (Cal Test: CT3134-S-9)	SET	6
4	Outer molded: 45P PVC, color: Black .	G	40
3	Screw: E4.0*30.5mm(#4-40UNC) molded Black .	PCS	2
2	P1 CONN: DB 37Pin Male Inside black Pin gold flash .	PCS	1
1	Cable: 20AWG cable. (Cal Test: Red: CT2879-2-10, Black: CT2879-0-10, Green: CT2879-5-10, Blue:CT2879-6-10, Yellow: CT2879-4-10, White: CT2879-9-10).	MM	
ITEM	DESCRIPTION	UNIT	QTY

X ±	X° ±	NAME:			
.X ±	.X° ±	W1			
.XX ±	.XX° ±	UNITS:	PART NO.:	TITLE:	
		MM	DNA-CBL-261	DNx-DMM: cable pinout	
			TOM	RFQ NO.:	
APPD BY	CHECK BY	DRAWN BY		SCALE	SHEET
			NONE	1/1	REV. A