

P1


PIN OUT

P2

| P1 |           | P2 |
|----|-----------|----|
| 1  | _____     | 1  |
| 2  | _____     | 2  |
| 3  | _____     | 3  |
| 4  | _____     | 4  |
|    | ⋮         |    |
| 25 | _____     | 25 |
| 26 | _____     | 26 |
| 27 | _____     | 27 |
|    | ⋮         |    |
| 34 | _____     | 34 |
| 35 | _____     | 35 |
| 36 | _____     | 36 |
| 37 | _____     | 37 |
| S  | D.W+Braid | S  |

Note: P1 and P2 Inside the molded must use copper foil and solder the braid 360 degree to the shell .

| Item | DESCRIPTION  | UNIT | QTY |
|------|--|------|-----|
| 5    | PVC : 45P PVC , Color:Black/BK01-A .   | KG   |     |
| 4    | Screw :4.0*30.5mm( #4-40UNC )Material Screw .  | PCS  | 4   |
| 3    | P2 CONN: DB 37Pin Female Inside black Pin gold flash .                                       | PCS  | 1   |
| 2    | P1 CONN: DB 37Pin Male Inside black Pin gold flash .   | PCS  | 1   |
| 1    | Cable: UL2464 26AWG(7/0.16TC)*37C+AL/MY+D.W+Braid, OD=9.0±0.15mm, Jacket Color:Black/BK01-A. | MM   |     |

|   |          |          |                                    |                       |      |
|---|----------|----------|------------------------------------|-----------------------|------|
| X ±   | X° ±     | NAME:    | UNITED ELECTRONIC INDUSTRIES, INC. |                       |      |
| .X ±  | .X° ±    | W1       |                                    |                       |      |
| .XX ±   | .XX° ±   | UNITS:   | PART NO.:                          | TITLE:                |      |
|   |          | mm       | DNA-CBL-37S                        | 37-pin shielded cable |      |
|  |          |          | GX                                 | DW 3 NO.:             |      |
|   |          |          | 2006/11/01                         | RFQ#UEI0261026-01     |      |
| APPD BY   | CHECK BY | DRAWN BY | SCALE                              | SHEET                 | REV. |
|   |          |          | NONE                               | 1/1                   | A    |