Company Proprietary Data

		Certi	ficate	of Volatility					
Model: Part Number:		Manufacturer: United Electronic Industries, Inc							
DNA-PPCx-1G			Street Address: 27 Renmar Ave						
						e: MA Zip: 02081			
		V		Memory	Statt		Lipt 02001		
Does the item contain volatile	memory (i.e., memo				ed)?				
$X \square$ Yes \square No	including (incl, include	ly whose e	oncento		cu).				
If the answer is 'Yes', please provide the following information for each type (use additional sheets if required):									
Type (SRAM, DRAM, etc.): Size:		User		Function:		Process to Clear:			
DRAM	128 MB	Modifiable:		Scratch pad and temporary		Power off unit			
		X Ves	6	storage for firmware.					
Type (SRAM, DRAM, etc.):	Size:	User		Function:		Process to Clear:			
	Siller	Modifiable:		i unction.		Trocess to citure			
		Yes							
		□ No							
Type (SRAM, DRAM, etc.):	Size:	User Modifiable:		Function:		Process to Clear:			
		Viodinab	ne:						
Non-Volatile Memory									
Does the item contain non-vo	latile memory (i.e., m				r is ren	noved)?			
X Yes No									
If the answer is 'Yes', please				ach type (use additional sheet	s if rec	quired):			
Can this item contain Cache X Yes No				ion specifically chose to write	The	tondord AL	I doos not sunnor t		
	this function	a mai me a	аррпсан	ion specifically chose to write	. The s	stanuaru Ar	T does not suppor t		
Type (BBRAM, Flash, EEPR		User		Function:		Process to	Clear:		
etc.):	32	Modifiable:		Holds specific unit info sucl	lds specific unit info such as		Can be cleared with "special"		
FLASH	MByte	yte X Yes		serial number. Also holds u	ınit's		s, but clearing the		
				firmware and boot loader		memory would render the unit inoperative.			
Type (BBRAM, Flash, EEPR	OM, Size:	User		Function:		Process to			
etc.):		Modifiable:		runcuon.		11000510	Cical.		
		Yes							
		🗌 No							
Type (BBRAM, Flash, EEPR	OM, Size:	User Madifiables		Function:		Process to Clear:			
etc.):		Modifiable:							
			Me	dia					
Does the item contain media	storage capability (i.e	., removab			e drive	s, memory o	cards, etc.)?		
X Yes No						· ·			
If the answer is 'Yes', please			on for ea		s if rec		~		
Type (Disk, Tape, etc.):	Size:	User Madifiables		Function:		Process to Clear:			
SD Card Removable:	Up to 4 GB	Modifiable:		None in this version of the chassis		n/a			
X Yes No				U145515					
Type (Disk, Tape, etc.):	Size:	User		Function:	nction:		Clear:		
		Modifiab	le:						
Removable:									
YesNoType (Disk, Tape, etc.):	Size:	User		Function:		Process to	Clear		
rype (Disk, rape, etc.):	Size:	User Modifiab	le:	runcuon.		r rocess to	Ural.		
Removable:		Yes							
🗌 Yes 🗌 No		🗌 No							

The information contained on this form shall be considered <u>Company Proprietary Data</u> furnished by the item manufacturer. The data shall be released only to customer employees or US Government representatives as necessary to accomplish the intended task (i.e., obtaining approval to operate a system processing classified data and incorporating the described item). The data shall not be disseminated to other vendor/contractor personnel without the express written authorization of the manufacturer.

Additional Information:

UEI's PowerDNA Cubes do not store any data, input or output, in any non-volatile memory unless the writing of this data is specifically implemented in the customer software. All data written to and/or read from PowerDNA chassis is lost within seconds of power loss or if the power switch is turned off.

The only exception to this rule is the user, either via the API or PowerDNA Explorer, may store default "power on" and "emergency shut-down" output conditions/states of the analog and digital output devices. Note that even this data is ONLY written to non-volatile memory upon specific instructions either from PowerDNA Explorer or the appropriate API call and never from standard data I/O functions.

A jumper on the Power-1GB board (part of the CPU module) allows the user to select whether writing to non-volatile FLASH memory is enabled or disabled. When set in the disable position, writes to FLASH are disabled in hardware as the jumper disables the write control line on the memory. Note that when these writes are disabled, the firmware on the chassis cannot be updated. For this reason most customers choose to do their development with the write enabled, and then move the jumper to disabled for deployment.

Though hardware for an SD card (and USB) interface is provided, with the version of Firmware and Software provided in this version of the chassis (DNA-PPCx-1G), there is no ability to read or write data to or from an SD card.

Validation Test							
Does the item have a validation test method? (to determine that it has been returned to default settings, cleared, flushed) $X \square Yes \square No$							
If the answer is 'Yes', please provide the following information for each type (use additional sheets if required):							
Additional Information:							
Powering the unit off will flush all dynamic memory. During reboot after power-up, all factory default							
settings are reset except for the unit's IP addresses.							
Vendor Representative Information							
Name:	Title:	Office Phone:	Fax/Email:				
Robert Judd	Director of Mktg	508-921-4557	bjudd@ueidaq.com				

The information contained on this form shall be considered <u>**Company Proprietary Data**</u> furnished by the item manufacturer. The data shall be released only to customer employees or US Government representatives as necessary to accomplish the intended task (i.e., obtaining approval to operate a system processing classified data and incorporating the described item). The data shall not be disseminated to other vendor/contractor personnel without the express written authorization of the manufacturer.